

AV-04FDI

ENTRANCE PANEL



Description

BAS-IP AV-04FDI — stylish vandal-proof panels with installation by the flush mount method. Each panel provides a perfect video image and sound transmission to the indoor monitors.

These individual entrance panels are suitable for installation both in apartments and in offices, factories, gas stations, etc.

There is also the possibility of individual text or logo appliance on the panel (through in the service center).

Specifications

Panel type	**Induvidial**
Induction Loop	**Yes**
Camera	**1/4”**
Resolution	**2 Mpx**
Camera angle	**100° (horizontal)**
Output video	**HD (1280 × 720), H.264 Main Profile**
Call button	**Mechanical**
Night backlight	**6 LEDs**
Light sensitivity	**0,01 LuX**
Protection class	**IP65**
IK-Code	**IK07**
Working temperature	**-40 — +65 °C**
Power consumption	**6,5 W, in standby — 3,6 W**
Power supply	**PoE, +12 V DC**
Body	**Aluminum**
Colors	**Black / Silver**
Dimensions for installation	**85 × 180 × 45 mm**
Size of the panel	**95 x 190 x 27 mm**
Installation	**Flush mount**

Main features

- Camera resolution 2.0 MP
- Software Link support
- Mechanical button
- Protection class IP65
- Flush mounting
- IK-Code IK07
- PoE and +12V DC
- Aluminum case
- Open API
- Working temperature -40 – +65 °C

The specifications and appearance of the device may differ from those stated or may change without prior notice.

Functional capabilities

Interface	**Multi-language graphical and WEB interface**
Lock opening	**By means of a monitor** **By QR code** **By guest link** **The BAS-IP Intercom app** **The BAS-IP Link app** **From API**
Identifiers in the panel memory (QR codes, cards, key fobs, UKEY, access codes)	**20 000**
Connection of the additional SH-12 module and its support	**Wiegand input: from 6 to 128 bits inclusive** **Wiegand output for card, key fob, UKEY, QR, Face, Digital code, and all other types of identifiers: from 26 to 128 bits inclusive.**
Shortcut buttons	**1 mechanical call button**
Authentication	**WEB – interface and RTSP stream**
Additionally	**Software Link support, SIP P2P, Built-in relay, Open API, Hermetic back cover**

Color variations



BLACK



SILVER

Appearance and mechanical mounting

