



BBC BIRCHER

Smart Access









ClickLine
CoverLine
StandardLine

Electrical safety edges and rubber profiles with 20 mm contact strips for automatic gates, doors, public transport and industrial applications

Reliable, proven, suitable for self-assembly

- **Suitable profile for every application**
- **Best electrical properties**
- **High mechanical load capacity**
- **Quick mounting with special profile shapes**
- **Conformity acc. to EN ISO 13856-2, EN 12978**

bircher.com

Electrical safety edges

For automatic gates, doors, public transport and industrial applications




Reliable, tried-and-tested as the best


Electrical safety edges are used for protecting crushing and shearing points on automatic gates, doors, shutters and grills. Profiles of different sizes in combination with various switching devices safely and reliably protect people and objects according to the applicable standards.

Quick and easy to install

Our safety edges are based on the tried-and-tested principle of the contact strip drawn into the rubber profile. They are available both prefabricated at the factory and as system parts for self-assembly by the customer. The ingenious structure with separate contact strips can be relied upon for high reliability even in unusual applications and facilitates retrofitting on site.



Safety edges – system overview



End pieces

Maximum flexibility


End pieces are available with or without terminating resistor (standard 8.2 kOhm) and with various cable lengths.



Safety edge assembly

Pre-assembled – individual and convenient


For optimum functionality, a distinction can be made between horizontal and vertical application:



① Rubber profile sealed **on both ends** with end caps
→ primarily for horizontal safety edge application
② Rubber profile **closed at top** with end cap,
open at bottom with profile holder
→ for vertical safety edge application only

Self-assembly – quick and easy

Safety edges can be self-assembled without problems and within the quickest possible time




Detailed installation and operating instructions are included with the product



Contact strip ENT-R – perfect sensor

This robust contact strip is especially suited for applications in moist conditions or with a large mechanical load










Reliable in every application

Situation
Sliding gate

Solution
- Safety edge (ClickLine or CoverLine) in combination with the radio transmission system ExpertSystem XRF


Advantages
- Optimum protection because of mobile and stationary safety edges acc. to cat. 2 or cat. 3
- Tip: ProLoop2, reliable monitoring and evaluation of induction loops as opening sensor



Situation
Sectional gate

Solution
- Safety edge (ClickLine, CoverLine or StandardLine) in combination with the radio transmission system ExpertSystem XRF


Advantages
- Optimum protection because of mobile safety edges acc. to cat. 2 or cat. 3
- Tip: Herkules 2E gate radar as opening sensor. It distinguishes between vehicles and people



Situation
Folding door

Solution
- Safety edge (ClickLine, CoverLine or StandardLine) in combination with the radio transmission system ExpertSystem XRF


Advantages
- Optimum protection because of mobile safety edges acc. to cat. 2 or cat. 3
- Tip: Depending on the gate height, Herkules 2E or Merkur 2 as reliable opening sensor



Situation
Revolving door

Solution
- Safety edge (ClickLine, CoverLine or StandardLine) in combination with a switching device

Tip
- Merkur 2 as reliable opening sensor




ClickLine

Rubber profiles with click-fit foot









Click-fit!
The easiest possible installation is a feature of ClickLine: Click and go. No need for time-consuming pushing in from the side. This means even damaged safety edges can be renewed quickly and effortlessly. The optimally designed profile shape also guarantees the greatest possible switching reliability.



ClickLine profile types

General technical data on rubber profiles and prefabricated safety edges can be found on the back page.

Dimensions (Dimensions in mm, tolerances acc. to DIN ISO 3302-1, tl. E2)						
Rubber profile	EPE025/029A0V	EPE030/042A0V	EPE030/042J2V	EPE036/045A0V	EPE036/045J2V	EPE036/065A0V
Article no.	210736	210751	210752	210760	210761	210764
Packing unit	50 m	50 m	50 m	25 m	25 m	25 m
Aluminium rail (max. length 6 m)	AP-5 / AP-5-F1	AP-5 / AP-5-F1	AP-5 / AP-5-F1	AP-8	AP-8	AP-8
Safety edges (prefabricated)	ELE025/029A0Vx	ELE030/042A0Vx	ELE030/042J2Vx	ELE036/045A0Vx	ELE036/045J2Vx	ELE036/065A0Vx
Activation distance*	7 mm	6 mm	10 mm	11 mm	15 mm	10 mm
Switch point force*	70 N	60 N	100 N	110 N	90 N	140 N
Overtravel*						
250 N	8 mm	18 mm	5 mm	14 mm	17 mm	23 mm
400 N	10 mm	20 mm	14 mm	17 mm	20 mm	29 mm


*acc. to EN ISO 13856-2, temp. 23 °C, test object ø 80 mm, measuring point C3

CoverLine

Rubber profiles for high visual requirements







The synthesis of practicality and appearance
The aluminium profile is covered by the lateral attachment principle. This results in a uniform appearance that blends very well even into even demanding designs. The installation is quick and easy: simply click in, no need for pulling in sideways. CoverLine is especially suitable for vertical installation (sliding gate at site entrances) and for long overtravel distances. Specially developed profiles guarantee the highest switching reliability.



CoverLine profile types

General technical data on rubber profiles and prefabricated safety edges can be found on the back page.

Dimensions (Dimensions in mm, tolerances acc. to DIN ISO 3302-1, tl. E2)				
Rubber profile	EPE040/055A0J	EPE040/067A0J	EPE040/081A0J	EPE040/105A0J
Article no.	210766	354468	262476	219341
Packing unit	30 m	20 m	20 m	25 m
Aluminium rail (max. length 6 m)	AP-G1	AP-G1	AP-G1	AP-G1
Safety edges (prefabricated)	ELE040/055A0Jx	ELE040/067A0Jx	ELE040/081A0Jx	ELE040/105A0Jx
Activation distance*	10 mm	5 mm	8 mm	5 mm
Switch point force*	100 N	60 N	83 N	70 N
Overtravel*				
250 N	11 mm	30 mm	38 mm	37 mm
400 N	15 mm	32 mm	41 mm	53 mm

CoverLine is no longer available
Please contact our sales department for more information and information on replacement products.

The perfect and powerful alternative to the discontinued CoverLine:

ExpertSystem XL
– highly sensitive
– economical
– attractive




StandardLine

Rubber profiles with standard mounting foot









The tried-and-tested, reliable profile family
StandardLine offers the widest range of contours for all kinds of applications. We will be happy to present additional versions on request.

EPDM, the robust material
All safety edges from Bircher are made from EPDM. It is totally resistant to various materials and substances such as waste water, acetone, manganese sulphate, methyl alcohol, methyl phthalate as well as adequate resistance to acetaldehyde, methyl ethyl ketone, methyl chloride, cold lactic acid and other substances.



StandardLine profile types

General technical data on rubber profiles and prefabricated safety edges can be found on the back page.


Dimensions (Dimensions in mm, tolerances acc. to DIN ISO 3302-1, tl. E2)			Material: NBR (oil-resistant) 			
Rubber profile	EPE025/020A0K	EPE025/029A0K	EPN025/029A0K	EPE025/029D1K	EPE025/040A0K	EPE036/060A0D
Article no.	210732	210733	210824	210738	210746	210762
Packing unit	50 m	50 m	50 m	50 m	50 m	25 m
Aluminium rail (max. length 6 m)	AP-5 / AP-5-F1	AP-5 / AP-5-F1	AP-5 / AP-5-F1	AP-5 / AP-5-F1	AP-5 / AP-5-F1	AP-4
Safety edges (prefabricated)	ELE025/020A0Kx	ELE025/029A0Kx	ELN025/029A0Kx	ELE025/029D1Kx	ELE025/040A0Kx	ELE036/060A0Dx
Activation distance*	3 mm	7 mm	7 mm**	7 mm**	4 mm	5 mm
Switch point force*	70 N	80 N	80 N**	80 N**	70 N	90 N
Overtravel*						
250 N	2 mm	6 mm	6 mm**	6 mm**	9 mm	13 mm
400 N	4 mm	10 mm	10 mm**	10 mm**	12 mm	30 mm

*acc. to EN ISO 13856-2, temp. 23 °C, test object ø 80 mm, measuring point C3 **preliminary information, subject to change


Aluminium rails / switching devices

The matching aluminium rail


Aluminium rails from Bircher can be quickly and easily installed. Simply screw on, push in or click on the profile, and that's it.




AP-5
Article no. 209583 (6.1 m)
Article no. 209588 (2 m)




AP-8
Article no. 209593 (6.1 m)
Article no. 209595 (2 m)



AP-4
Article no. 209580 (6.1 m)
Article no. 209582 (2 m)



AP-5-F1
Article no. 311759 (6.1 m)



Calculation model

For selecting the suitable safety edge.

It is important to establish the stopping and overtravel distances in order to guarantee the greatest possible safety

Calculation of the stopping distance of hazardous parts (s_1):
$s_1 = ½ \times v \times T$

Calculation of the minimum overtravel of the safety edge s:
$s = s_1 \times C$

Key
v = Speed of the hazardous movement [mm/s]
T = Run-on time of the entire system (machine + safety edge) [s]
C = Safety factor, at least 1,2 (a greater safety factor should be selected if there are other factors such as a brake system which might be damaged; → EN ISO 13856-2)


The right switching device for every application

Some examples.

Details and technical data, including on additional switching devices and transmission systems, can be found in the corresponding booklets or by request from us.

Article no.	Description	
410975	**ExpertSystem XRF-1** Wireless signal transmission system cat. 2/3. Radio transmission system for automatic sectional, folding and sliding gates. Evaluation of mobile/stationary safety edges with terminating resistor 8.2 kOhm, supply voltage 12–36 V ACDC, dimensions 50 × 121 × 23 mm, set 1-channel: 1 receiver XRF-R1, 1 transmitter XRF-T2	
210979	**ESD3** Cat. 3 safety switching device. For 2 sensors 8.2 kOhm, 2 redundant outputs, positively driven relays, PLe, cat. 3 acc. to EN ISO 13849-1, mounting on DIN rail, supply voltage 24 V ACDC (voltage variants 115/230 V AC), dimensions 45 × 79 × 105 mm	

Order details



Order details for prefabricated safety edges

ELE030/042A0V	2	/	1	/	2500	/	2	/	8K

Type
See tables
ClickLine pg. 4
CoverLine pg. 5
StandardLine pg. 6


Contact strip
2 = ENT-R

Profile endings
1 = 8k2 resistor, with aluminium
2 = 2 cables, with aluminium
4 = 8k2 resistor, without aluminium
5 = 2 cables, without aluminium
A1 = 8k2 resistor, with alu., bottom open, cable at the top
A4 = 8k2 resistor, without alu., bottom open, cable at the top
B1 = 8k2 resistor, with alu., bottom open, cable below
B4 = 8k2 resistor, without alu., bottom open, cable below
C2 = 2 cables, with alu., bottom open
C5 = 2 cables, without alu., bottom open

Length
Length of edge [mm]

Cable
Length [m] / **resistor** (8K) **left/top**

Cable
Length [m] / **resistor** (8K) **right/down**



Order details for prefabricated contact strips

ENT-R	/	4	/	2500	/	2	/	8K

Type
ENT-R

End piece 2
4 = 8k2 resistor, cable
5 = 2 cables

Length
"L total" length of strip [mm]

Order details for components for self-assembly

Contact strip


Type	50 m roll	100 m roll	
ENT-R	ENT-R/50 **210718**	ENT-R/100 **210715**	

End pieces (packaging unit 10 pcs.)


Type	8k2	without		Cable	0.5 m	
Resist.	ENEH-8 **210642**	ENEH-0 **210626**				
Cable	ENEH-K05 **210649**	ENEH-K2 **210661**	ENEH-K4 **210670**	ENEH-K7 **210673**	ENEH-K10 **210654**	

Type	0.5 m	2 m	4 m	7 m	10 m	
Cable	ENEH-K05 **210649**	ENEH-K2 **210661**	ENEH-K4 **210670**	ENEH-K7 **210673**	ENEH-K10 **210654**	

End caps (packaging unit 50 pcs.)

209008 **250333** **256012**	**EN-C60** **EN-C29** **EN-C42**	End cap for rubber profile EPE036/045; /060; /065 End cap for rubber profile EPE025/029 End cap for rubber profile EPE030/042	
210616	**ENA-10**	Terminating band for rubber profile, 10 m roll (1 pc.), for cutting by customer	
219349	**EN-KAS**	End piece for arcing chamber	

Accessories / tools

209249 **209248**	**EN-DS** **EN-DL**	Sealing plug for arcing chamber, 50 pcs. Sealing plug with hole for cable, 50 pcs.	
210964	**ES-BD**	Sealing compound for profile seal, 1 bag with strips (sufficient for about 50 edges)	
211010	**ES-KLEBER**	Contact adhesive for sealing plugs, 20 g tube (sufficient for about 50 edges)	
211739	**ES-PRESS**	Pliers with jaws, bag of 1 (for pressing the end pieces onto the contact strips)	
212876	**PROFIL-SCHERE**	Profile cutters, bag of 1 (for cutting a rubber profile)	
262494	**EN-PHK**	Profile holder for ClickLine and StandardLine, 10 pcs.	
210617 **210618** **210619**	**EN-A20** **EN-A30** **EN-A40**	Delimiter piece, height 18 mm, 10 pcs. Delimiter piece, height 28 mm, 10 pcs. Delimiter piece, height 38 mm, 10 pcs.	

Technical data

ENT-R contact strips	
Dimensions (max.)	7.5 × 19 mm
Operating temperature	–25 °C to +60 °C
Storage temperature	–40 °C to +80 °C
Material	EPDM
Contact material	Conductive EPDM
Current (min. / max.)	1 mA / 100 mA
Max. voltage	30 V AC/DC
Resistance per unit length	< 2 Ohm/m
Contact resistance	Typ. < 200 Ohm, max. < 500 Ohm
Switching frequency	> 100'000 (with test object ø 80 mm)

Prefabricated safety edges	
Temperature range	–20 °C to +55 °C
Max. length	6 m (longer lengths on request)
Insulating strength	1500 V AC
Max. load capacity	500 N
Dead zone	20 mm (ELE040/105A0J2: 0 mm)
Switching frequency	> 10'000 (with test object ø 80 mm)
Connection cable	Double-jacketed cable, PVC, UV- and weatherproof, ø 4.7 mm, strain relief wire 2 x 0.34 mm², min. bending radius 10 mm, non-detachable
Protection class	IP65
Standards conformity	EN 12978, EN ISO 13856-2

Note
Technical details and recommendations concerning our products are based on experience and are an aid for the orientation of the user. Details stated in our brochures and data sheets do not guarantee special properties of the products. This does not apply to special product properties confirmed in writing or individually on a case-by-case basis. Subject to technical alterations.

BBC Bircher Smart Access
Wiesengasse 20
8222 Beringen
Switzerland
Phone +41 52 687 11 11
info@bircher.com
bircher.com